

WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

	Operating Weight	Tipping Load		Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length		
		Straight	Full Turn						
ROPS Canopy (Instead of ROPS Cab)	lb (kg)	-440 (-200)	-395 (-180)	-330 (-150)	in (mm)				
Remove ROPS Cab (for transport only)	lb (kg)	-1100 (-500)	-990 (-450)	-835 (-380)	in (mm)				
Remove Optional Counterweight	lb (kg)	-730 (-330)	-1210 (-550)	-1035 (-470)	in (mm)				
Tires: 23.5-25-12PR (L-2)	lb (kg)	-440 (-200)	-485 (-220)	-420 (-190)	in (mm)				
20.5-25-16PR (L-2)	lb (kg)	-1985 (-900)	-1430 (-650)	-1210 (-550)	in (mm)	-1 ⁹ / ₁₆ " (-40)	+1 ⁹ / ₁₆ " (+40)	-2 ³ / ₁₆ " (-60)	+1 ¹⁵ / ₁₆ " (+50)
20.5-25-16PR (L-3)	lb (kg)	-1765 (-800)	-1280 (-580)	-1080 (-490)	in (mm)	-1 ⁹ / ₁₆ " (-40)	+1 ⁹ / ₁₆ " (+40)	-2 ³ / ₁₆ " (-60)	+1 ¹⁵ / ₁₆ " (+50)
20.5-25-16PR (L-2) with 75% CaCl ₂	lb (kg)	-185 (-85)	-220 (-100)	-175 (-80)	in (mm)	-1 ⁹ / ₁₆ " (-40)	+1 ⁹ / ₁₆ " (+40)	-2 ³ / ₁₆ " (-60)	+1 ¹⁵ / ₁₆ " (+50)
20.5-25-16PR (L-3) with 75% CaCl ₂	lb (kg)	-35 (-15)	-45 (-20)	-20 (-10)	in (mm)	-1 ⁹ / ₁₆ " (-40)	+1 ⁹ / ₁₆ " (+40)	-2 ³ / ₁₆ " (-60)	+1 ¹⁵ / ₁₆ " (+50)
Air conditioner—Deletion	lb (kg)	-220 (-100)	-265 (-120)	-220 (-100)	in (mm)				
Belly Guard (rear frame)	lb (kg)	+155 (+70)	+175 (+80)	+155 (+70)	in (mm)				

Base Tire 23.5-25-16PR (L-3)

Tread 6'9¹/₈" (2060mm)

Width (outside tire) 8'9¹/₂" (2680mm)

Width (outside bucket) 9'2¹/₄" (2800mm)

Equipped with GSC bucket with bolt on cutting edge

23.5-25-16PR (L-3) Tire and ROPS Cab

