

## WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

		Operating Weight	Tipping Load			Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length
			Straight	Full Turn					
Remove ROPS Cab (for transport only)	lb (kg)	-1100 (-500)	-990 (-450)	-860 (-390)	in (mm)			-6 <sup>7</sup> / <sub>8</sub> " (-175)	
Remove Optional Counterweight	lb (kg)	-790 (-360)	-2030 (-920)	-1740 (-790)	in (mm)				-3 <sup>15</sup> / <sub>16</sub> " (-100)
Tires: 26.5-25-20PR (L-2)	lb (kg)	-400 (-180)	-310 (-140)	-265 (-120)	in (mm)				
26.5-25-20PR (L-4)	lb (kg)	+1060 (+480)	+790 (+360)	+670 (+305)	in (mm)				
26.5-25-20PR (L-5)	lb (kg)	+1850 (+840)	+1380 (+625)	+1180 (+535)	in (mm)				
26.5-25 (75% CaCl <sub>2</sub> )	lb (kg)	+3220 (+1460)	+4810 (+2180)	+4120 (+1870)	in (mm)				
Air conditioner—Deletion	lb (kg)	-220 (-100)	-240 (-110)	-220 (-100)	in (mm)				
Belly Guard (rear frame)	lb (kg)	+410 (+185)	+600 (+270)	+510 (+230)	in (mm)				

Base Tire 26.5-25-20PR (L-3)

Tread .....7'3<sup>13</sup>/<sub>16</sub>" (2230mm)  
 Width (outside tire) .....9'7<sup>3</sup>/<sub>8</sub>" (2930mm)  
 Width (outside bucket) .....10'2<sup>1</sup>/<sub>16</sub>" (3100mm)

Equipped with GSC bucket with bolt-on cutting edge, optional counterweight  
 26.5-25-20PR (L-3) Tire and ROPS Cab

